

(ALL DIMENSIONS ARE IN MILLIMETERS)
 ΔM20X1.5-6H ISO (METRIC) THREAD
 19,026/19,216 PITCH DIA.



* SOCKET WRENCH CLEARANCE DIAMETER .
RECOMMENDED MAXIMUM L.S. DEPTH
WITHOUT SOCKET CLEARANCE: 36,53
MINIMUM CENTERLINE-TO-EDGE
DISTANCE: 15,88
MINIMUM CENTERLINE-TO-CENTERLINE
DISTANCE: 26,98
NBOM CALLOUT: SUN STD T-61A CAVITY
NBOM CODE: T61A

**ALL O-RING "LEAD-IN's" TO BE
SMOOTH AND FREE OF NICKS AND
SHARP EDGES.

PROPRIETARY NOTICE
THIS DRAWING DESCRIBES A
PROPRIETARY PRODUCT OF
SUN HYDRAULICS CORPORATION
AND MAY NOT BE REPRODUCED OR
GIVEN TO A THIRD PARTY WITHOUT
WRITTEN PERMISSION FROM
SUN HYDRAULICS CORPORATION
© SUN HYDRAULICS CORPORATION

[illegible]

REVISION	PART NO.	T-61A	METRIC
D	SHEET	2	of 3